

## LIFT CHECK VALVE

### FEATURES

- Suitable For Industrial, Pneumatic and Hydraulic Installations
- Ideal For Hot/ Cold Water, Different Oils and Compressed Air
- Can be Fitted in Horizontal, Vertical or Oblique Position



### TECHNICAL

- Code: VCLR-(size DN)
- Size Range: DN10-DN100
- Working Temp Range:
  - 20°C to 110°C (Air)
  - 0°C to 90°C (Water)
  - 20°C to 60°C (Gas)
- Thread: ISO228-DIN259-BS2779

### MATERIALS

- Body: Brass CW 617N
- Internal Seat: Stainless Steel Plate AISI 304 Fitted with NBR 60 SH/A, Cover Plate and Rod in Brass CW 614N
- Spring: Stainless Steel AISI 302

### DIMENSIONS

Size (DN)	H	L	Approx. Wt (kg)	kPa
10	55.0	34.5	0.17	2482
15	58.5	34.5	0.19	2482
20	65.0	41.5	0.27	2482
25	74.5	48.0	0.43	2482
32	83.0	60.5	0.54	1793
40	93.0	71.0	0.87	1793
50	101.0	87.0	1.32	1793
65	122.0	120.0	2.62	1172
80	141.5	140.5	4.21	1172
100	158.5	172.5	6.13	1172

